

# CRYOMECH

## Liquid Nitrogen Plant Specification Sheet

### LNP20

Liquid nitrogen production rate\*  $\geq 20$  liter/day (0.8 liter/hour); 5.2 gal/day (0.22 gal/hour)  
\*reduced production rate on 50Hz

#### Dewar assembly

Capacity 100 liters (26 gal)  
Weight:  
Empty 210 lb (95 kg)  
Full 388 lb (176 kg)  
Dimensions (OD x H) 24 x 48 in (61 x 122 cm)

#### Cold head model

AL125, mounted on dewar

#### Helium compressor model

CP830, available as air or water cooled

##### Air cooled:

Weight 176 lb (80 kg)  
Dimensions (L x W x H) 19 x 22 x 22 in (48 x 56 x 56 cm)  
Electrical rating 208/230VAC, 1Ph, 60Hz // 200/220VAC, 1Ph, 50Hz  
Power consumption 4.1 kW // 3.5 kW

##### Water cooled:

Weight 165 lb (75 kg)  
Dimensions (L x W x H) 18 x 18 x 22 in (46 x 46 x 56 cm)  
Electrical rating 208/230VAC, 1Ph, 60Hz // 200VAC, 1Ph, 50Hz  
Power consumption 3.9 kW // 3.3 kW  
Cooling water flow rate Minimum flow 1.2 GPM (4.5 LPM) @ 80°F (27°C) maximum temperature

#### Helium flexible lines

Standard length 10 ft (3 m)  
Weight per pair 6.4 lb (2.9 kg)

#### Nitrogen generator assembly

Nitrogen purity 98%  
Weight 61 lb (28 kg)  
Dimensions (L x W x H) 42 x 7 x 29 in (107 x 18 x 74 cm)  
Nitrogen Gas Flow Rate 0.38 SCFM at 7 PSIG (10.8 LPM at 0.5 bar)

#### System parameters

Helium pressure 200  $\pm$  5 PSIG (13.8  $\pm$  .34 bar) @ 60 Hz  
200  $\pm$  5 PSIG (13.8  $\pm$  .34 bar) @ 50 Hz  
Ambient temperature range 45°F to 100°F (7°C to 38°C)  
Maximum altitude (standard LNP) 10,000 ft (3000 m)

# CRYOMECH

## Liquid Nitrogen Plant Specification Sheet

### LNP20

#### Compressed air requirement

Dew point

35°F (2°C)

Flow rate

3.7 ACFM at 85 PSIG (105 ALPM at 6 bar) FAD\*\*

\*\*FAD (free air delivery) measures the compressor's output while operating at a specific pressure. The result, expressed in actual cubic feet per minute (ACFM), rates the outlet flow based on the inlet conditions.

#### Maximum sound level

Air cooled

76 dBA @ 1 meter

Water cooled

70 dBA @ 1 meter

#### Minimum footprint requirement

Air cooled helium compressor

7.5 x 2.5 ft (2.3 m x 0.8 m)

Water cooled helium compressor

4.5 x 3.5 ft (1.4 m x 1.1 m)

#### Shipping weight and dimensions

The standard LNP is packaged in two wooden crates

Crate 1(Cold Head, Dewar):

Weight

380 lb (172 kg)

Dimensions (L x W x H)

41 x 38 x 65 in (104 x 97 x 165 cm)

Crate 2(Helium Compressor):

Weight

440 lb (200 kg)

Dimensions (L x W x H)

48 x 40 x 38 in (122 x 102 x 97 cm)

Crate 3(Optional Air Compressor):

Weight

880 lb (399 kg)

Dimensions (L x W x H)

69 x 43 x 64 in (175 x 109 x 163 cm)

#### **Optional Equipment**

##### Air compressor

Flow rate

6.3 ACFM at 175 PSIG (178 ALPM at 12.1 bar) FAD

Weight

500 lb (227 kg)

Dimensions (L x W x H)

53 x 28 x 48 in (135 x 71 x 122 cm)

Duty cycle

1/3

Horsepower

3

Electrical rating

230VAC, 1Ph, 60Hz; 200VAC, 1Ph, 50Hz

Sound level

76 dBA @ 1meter

##### Refrigerated air dryer

Nominal capacity

10 SCFM (283 SLPM)

Weight

42 lb (19 kg)

Dimensions (L x W x H)

18 x 8 x 18 in (46 x 20 x 46 cm)

Power consumption

0.2 kW

Electrical rating

115VAC, 1Ph, 60Hz; 230VAC, 1Ph, 50Hz

113 Falso Drive, Syracuse, NY 13211 USA

315.455.2555 v 315.455.2544 f cryosales@cryomech.com www.cryomech.com